

WAN Feature

- WAN1: SFP Interface for Connection to Fiber
- WAN2: Gigabit Ethernet • IPv4:
- DHCP Client, Static IP, PPPoE, PPTP, L2TP, 802.1q Multi-VLAN Tagging
- IPv6:
- Tunnel Mode: TSPC, AICCU, 6rd, Static 6in4 - Dual Stack: PPP, DHCPv6 Client, Static IPv6
- USB WAN • PPP/DHCP
- WAN Connection Failover
- WAN Budgets*
- Load-Balance/Route Policy

Network Feature

- DHCP Client/Relay/Server
- IGMP Snooping/Proxy V2 and V3
- Dynamic DNS
- NTP Client
- Call Scheduling RADIUS Client
- DNS Cache/Proxy and LAN DNS
- UPnP 30 sessions
- Multiple Subnets
- Port-based/Tag-based VLAN (802.1g)
- Routing Protocol:
- Static Routing
- RIP V2

VPN

- Up to 50 VPN Tunnels
- Protocol : PPTP, IPsec, L2TP, L2TP over IPsec
- Encryption : MPPE and Hardware-based
- AES/DES/3DES
- Authentication : MD5, SHA-1 • IKE Authentication : Pre-shared Key and
- Digital Signature (X.509)
- LAN-to-LAN, Teleworker-to-LAN
- DHCP over IPsec
- IPsec NAT-traversal (NAT-T)
- Dead Peer Detection (DPD)
- VPN Pass-through
- VPN Wizard
- mOTP

* Firmware Upgradeabl

991-29<u>25000-Fiber</u>

- SSL VPN: 25 Tunnels
- VPN Trunk (Load Balance/Backup)
- Support Central VPN Management

Firewall

- Multi-NAT, DMZ Host, Port-redirection and Open Port
- Object-based Firewall, Object IPv6,
- Group IPv6
- MAC Address Filter
- SPI (Stateful Packet Inspection) (Flow Track)
- DoS/DDoS Prevention
- IP Address Anti-spoofing
- E-mail Alert and Logging via Syslog Bind IP to MAC Address
- Time Schedule Control
- User Management

Bandwidth Management

- QoS :
 - Guarantee Bandwidth for VoIP Class-based Bandwidth Guarantee by
 - User-defined Traffic Categories • DiffServ Code Point Classifying
 - 4-level Priority for Each Direction (Inbound
 - (Outhound)
- Bandwidth Borrowed
- Session Limitation
- Bandwidth Limitation
- Layer-2 (802.1p) and Layer-3 (TOS/DSCP) QoS Mapping

Network Management

- Web-based User Interface (HTTP/HTTPS)
- Quick Start Wizard
- CLI (Command Line Interface, Telnet/SSH)
- Administration Access Control
- Configuration Backup/Restore
- Built-in Diagnostic Function
- Firmware Upgrade via TFTP/FTP/HTTP/TR-069
- Logging via Syslog
- SNMP Management MIB-II (v2/v3)
- Management Session Time Out
- 2-level Management (Admin/User Mode) TR-069
- TR-104

www.draytek.com E-mail:info@draytek.com Tel:+886 3 597 2727 Fax:+886 3 597 2121

narks and brand names are the properties of their respective owners. ations subject to change at any time without notice, for more information please visit www.dravtek.com.or.contact your local rep

- LAN Port Monitoring
- Support Smart Monitor (Up to 50 nodes)
- Central AP Management (Up to 20 APs)
- 1 x 10/100/1000Base-TX, RJ-45 (WAN2) • 4 x 10/100/1000Base-TX LAN, RJ-45 Configurable Physical DMZ on Port1

Hardware Interface

- 2 x Detachable Antennas
- 2 x USB Host 2.0
- 1 x Factory Reset Button
- 1 x Wireless On/Off/ WPS Button

CSM (Content Security Management)

Vigor2925Fn

Dray Tek

Vigor2925Fn

Dual-WAN Security Router

Flexible Network Management

Vigor2925Fn is the IPv6 ready dual WAN broadband

security firewall router. It ensures the business continuity

for today and the future IPv6 network. Its gigabit Ethernet

WAN port can accept various high-speed Ethernet-based

WAN links via FTTx/xDSL/Cable. The 2 USB ports are for

3G/4G LTE mobile broadband access. With the multi-

WAN accesses, Vigor2925Fn supports bandwidth

management functions such as failover and load-

balancing, making them ideal solutions for reliable and

flexible broadband connectivity for the small business

The specifications cover many functions that are required

by modern day businesses, including secure but easy to

apply firewall, comprehensive VPN capability, Gigabit

LAN ports, USB ports for 3G/4G mobile dongles, FTP

servers and network printers, VLAN for flexible

The Gigabit Ethernet WAN port caters for any type of

Internet access, including FTTx, xDSL and Cable fitting

your local infrastructure. You can then use both WAN 1

and WAN 2 for failover, ensuring that you will always

have an access to the Internet even if one of the WAN

fails, or for load-balancing so the 2 WANs share Internet

Through mobility, brought by cellular networks, you can

connect 3.5G/4G USB mobile to 2.0 version USB port on

Support IPv6 & IPv4 network

office.

workgroup management.

load-balancing

Vigor2925Fn.

(FC

Dual WAN ports for failover and

traffic requirements of your organization.

Multi-task USB functionalities

- IM/P2P Application
- GlobalView Web Content Filter (Powered by **commtouch**°)
- URL Content Filter
- URL Keyword Blocking
- (Whitelist and Blacklist)
- Java Applet, Cookies, Active X, Compressed, Executable, Multimedia File Blocking
- Excepting Subnets

USB

- 3.5G (HSDPA)/4G (LTE) as WAN
- Printer Sharing

Wireless AP

• Wireless Client List

• 64/128-bit WEP

Wireless Wizard

• WPA/WPA2

• Hidden SSID

Multiple SSID

WPS

Wireless LAN Isolation

MAC Address Access Control

WDS (Wireless Distribution System)

• IEEE802.11e: WMM (Wi-Fi Multimedia)

1 x 100/1000Mbps Port, SFP Slot (WAN1)

SSID VLAN Grouping with LAN Port

Access Point Discovery

802.1x Authentication

Wireless Rate-control

(Port-based VLAN)

Frequency


- File System : Support FAT32 File System
- Support FTP Function for File Sharing
- Support Samba for File Sharing

note: LTE USB mobile Support List Please Contact support@draytek.com

802.11n WLAN with Single Band 2.4 GHz



Dual WAN ports for failover and load-balancing Object-based SPI Firewall and CSM (Content Security Management) for network security 2 x USB 2.0 ports for 3G/4G mobile, FTP server and network printers



This can be a backup broadband connection if the primary fixed line drops. You can connect USB disk or hard-drive to USB port for memory storage and file sharing. The Vigor2925Fn provides you with FTP access file uploading/downloading, which can be used from the local LAN or from anywhere on the Internet. The access can be using "username and password" or 'public'. Each of them can have their own directories and/or file access rights. The two WANs and USB mobile (connected to USB port) can be used either for WAN-backup or load balancing.

Secured networking

DrayTek Vigor2925Fn inherited versatile firewall mechanism from previous Vigor series routers. The object-based design used in SPI (Stateful Packet Inspection) firewall allows users to set firewall policy with ease. Object-based firewall is flexible and allows your network be safe. DoS/DDoS prevention and URL/Web content filter strengthen the security outside and control inside. The enterprise-level CSM (Content Security Management) enables users to control and manage IM(Instant Messenger) and P2P (Peer-to-Peer) applications more efficiently. The CSM hence prevents inappropriate content from distracting employees and impeding productivity. Furthermore, the CSM can keep office networks threat-free and available.

By adoption of the world-leading Commtouch GlobalView Web Content Filtering, you can block whole categories of web sites (e.g. sports, online shopping), subject to an annual subscription to the Commtouch GlobalView WCF. which is timely updated with changed or new site categorizations. A free 30-day trial can be activated via activation wizard of WUI.

Dray Tek

The "User Management" implemented on your router firmware can allow you to prevent any computer from accessing your Internet connection without a username or password. You can set scheduler or maximum usage time to your employees within office network. The user accounts can also be restricted by any other aspect of the firewall rule on a user-by-user basis.

Vigor2925Fn supports DrayTek's SmartMonitor network traffic analyzer (up to 50 users), which captures actual live data of activities in your managed network, such as the content of MSN entering to or out of your network. You can track specified files download/upload or view statistics on data type activities to realize what corporate related information have been released accidentally or on purpose.



50 VPN tunnels; hardware based with comprehensive secure protocols

Up to 50 VPN tunnels are supported, each can be set to IPsec/PPTP/L2TP/L2TP over IPsec protocols, with hardware encryption of AES/DES/3DES. This level of VPN capability covers the requirements of most businesses for secure inter-office and remote data accessing. For the site-to-site application, Vigor2925Fn offers VPN load-balancing & backup to deliver the high performance and reliable remote access. For client-tosite, remote dial-in users can use up-to 25 SSL VPN tunnels to avoid the local network infrastructure limitation.

Multi-subnets

With the 4-port Gigabit switch on the LAN side provides extremely high speed connectivity for the highest speed local data transfer of any server or local PCs. The tagged VLANs (802.1q) can mark data with a VLAN identifier. This identifier can be carried through an onward Ethernet switch to specific ports. The specific VLAN clients can also pick up this identifier as it is just passed to the LAN. You can set the priorities for LAN-side QoS. You can assign each of VLANs to each of the different IP subnets that the router may also be operating, to provide even more isolation. The said functionality is tag-based Multi-subnet.

Each of the wireless SSIDs can also be grouped within one of the VLANs.

Centralized Management

The embedded Central VPN Management (CVM) will let network administrator register up to 16 remote routers but run concurrent remote management over 8 remote routers.

AP Management

APM provides the 3-step installation, plug-plug-press, and then wireless clients are able to enjoy surfing internet. Moreover, through the unified user interface of Draytek routers, the status of APs is clear at the first sight.


Flexible Network Management

Like all DrayTek routers, Vigor2925Fn supports comprehensive network management functions. For example, you can set username/password and directory/file access privilege for individual users as required. There are also routing/network tables, system log, debugging utilities, etc., making network administrators' jobs easy.


Other management features include SNMP, TR-069 and TR-104. TR-069 can be utilized with DrayTek's VigorACS SI management software to remotely monitor and manage the Vigor2925Fn.

There are many nodes of license for deploying VigorACS SI Central Management. Through "Self-hosted" or "Cloudbased" subscription, the deployed DrayTek Vigor routers can be managed for firmware upgrade, VPN establishment, real-time monitoring and obtain proper customer care.

Cloud-based Business Applications Utilization



Secured networking



VLAN for secure and efficient workgroup management



Vigor2925Fn

		QoS	Subnet
	VLAN 0 HR Dept.	Lowest	LAN 1
	VLAN 1 Finance Dept.	Low	LAN 2
SSID 1	VLAN 2 Sales Dept.	Highest	LAN 3
SSID 2	VLAN 3 R&D Dept.	High	LAN 4